




# **POLARIS<sup>®</sup>**

**PRODUCT BROCHURE**



# THE ORIGINAL IS STILL THE BEST.

Polaris® Pre-Insulated Connectors set the benchmark for professional quality when splicing or tapping into a primary power conductor. Since introducing the first pre-insulated connector over 35 years ago, Polaris has helped contractors and electricians work faster and safer, saving them time and money. When you need a pre-insulated connector, choose the preferred and trusted brand still asked for by name.



## A SOLUTION FOR EVERY APPLICATION

---

The all-in-one design of Polaris Pre-Insulated Connectors installs more easily without tape or additional tools. For wet or dry locations, for parallel runs of primary power conductors or connecting fine-stranded extra-flexible copper cable, there's a broad range of sizes, port numbers and configurations to match the needs of any professional.



# DESIGNED FOR EASY INSTALLATION

---

The innovative design and labor-saving features of every Polaris Pre-Insulated Connector go beyond just making connections faster. The ergonomic shape and pre-filled oxide inhibitor make installation simple and comfortable. Removable wire port plugs and set screw covers prevent infiltration of dirt or debris. It's easy to see why professionals choose Polaris.



## THE POLARIS DIFFERENCE

---

### REMOVABLE PLUGS

Secures entry port closures and ensures debris prevention

### ABRASION & CHEMICAL RESISTANT

Plastisol insulation for maximum protection

### PRE-FILLED WITH OXIDE INHIBITOR

Corrosion prevention for low-contact resistance connections

### HIGHLY CONDUCTIVE

Aluminum alloy construction for superior conductivity

### SMOOTH EXTERIOR FINISH

Ergonomic design is comfortable to grip when applying torque



From engineering to manufacturing, Polaris pre-insulated connectors are American-made in Odessa, Florida, since 1985.

# POLARIS<sup>®</sup> BLACK

Pre-Insulated Connectors

## THE ORIGINAL IS STILL THE BEST

Its easy to see why the industry's original pre-insulated connector is still the brand most asked for by name. Polaris Black offers dependable performance in any application, including mountable options, connectors with stacked ports for tight spaces and heavy-duty UL-rated connectors for parallel runs. Polaris Black: a pioneer in high-quality, effortless connections for over 30 years.



## THE BLACK DIFFERENCE

### Withstand the Elements

Black insulation for a lifetime of exceptional UV resistance

### Removable plugs

Secures entry port closures and ensures debris prevention

### Smooth Exterior Finish

Ergonomic design is comfortable to grip when applying torque

### Pre-filled with Oxide Inhibitor

Corrosion prevention for low-contact resistance connections

### ●●● Parallel Rated and UL Listed

Multiple parallel configurations tested for maximum ampacities

See page 18 for a full listing of parallel rated connectors

## MULTIPLE CONFIGURATIONS

### SINGLE-SIDE ENTRY



### DUAL-SIDE ENTRY



### OFFSET ENTRY



### IN-LINE ENTRY



### STACKED



### MOUNTABLE



# POLARIS BLACK SPECIFICATIONS

## Wire Type

Use with Class B and C conductors

## Dual Rated

AL9CU, 90C\*

## UL Listed

UL486A/B for 600V max

## Location

Dry locations only

## Material

6061-T6 aluminum alloy

Insulated with high dielectric strength plastisol for increased chemical and abrasion protection

## Temperature

Cold rated to -45°C

WIRE CONNECTOR



## SINGLE-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IT-4	4 - 14	2	1.21	1.24	1.36	75-95	1/8
IPL4-3		3	1.63	1.24	1.36	75-95	1/8
IPL4-4		4	2.06	1.24	1.36	75-95	1/8
IPL4-5		5	2.48	1.24	1.36	75-95	1/8
IPL4-6		6	2.90	1.24	1.36	75-95	1/8
IPL4-8		8	3.74	1.24	1.36	75-95	1/8
IPL4-10		10	4.59	1.24	1.36	75-95	1/8
IT-2	2 - 14	2	1.32	1.24	1.39	100-130	5/32
IT-1/0	1/0 - 14	2	1.68	1.55	1.74	135-170	3/16
IPL1/0-3		3	2.33	1.55	1.74	135-170	3/16
IPL1/0-4		4	2.98	1.55	1.74	135-170	3/16
IPL1/0-5		5	3.63	1.55	1.74	135-170	3/16
IPL1/0-6		6	4.28	1.55	1.74	135-170	3/16
IPL1/0-8		8	5.58	1.55	1.74	135-170	3/16
IT-2/0	2/0 - 14	2	1.78	1.55	1.77	150-195	3/16
IT-3/0	3/0 - 6	2	1.93	1.60	1.83	175-225	1/4
IPL3/0-3		3	2.71	1.60	1.83	175-225	1/4
IPL3/0-4		4	3.49	1.60	1.83	175-225	1/4
IPL3/0-5		5	4.27	1.60	1.83	175-225	1/4
IPL3/0-6		6	5.05	1.60	1.83	175-225	1/4
IPL250-3	250 - 6	3	3.01	2.01	2.29	230-290	5/16
IPL250-4		4	3.88	2.01	2.29	410-527	5/16
IPL250-5		5	4.74	2.01	2.29	410-527	5/16
IPL250-6		6	5.60	2.01	2.29	615-790	5/16
IPL250-8		8	7.32	2.01	2.29	820-1053	5/16
IPL350-3	350 - 6	3	3.55	2.13	2.68	280-350	5/16
IPL350-4		4	4.60	2.13	2.68	514-657	5/16
IPL350-5		5	5.65	2.13	2.68	514-657	5/16
IPL350-6		6	6.70	2.13	2.68	770-985	5/16
IPL350-8		8	8.80	2.13	2.68	1028-1314	5/16
IPL500-3	500 - 4	3	4.04	2.50	2.95	350-430	5/16
IPL500-4		4	5.19	2.50	2.95	631-806	5/16
IPL500-5		5	6.33	2.50	2.95	631-806	5/16
IPL500-6		6	7.48	2.50	2.95	946-1209	5/16
IPL500-8		8	9.77	2.50	2.95	1262-1612	5/16
IPL600-3	600 - 6	3	4.50	2.83	3.32	385-475	5/16
IPL600-4		4	5.80	2.83	3.32	810-1035	5/16
IPL600-6		6	8.40	2.83	3.32	1215-1554	5/16
IPL750-3*	750 - 250	3	4.90	2.75	3.46	385-475	3/8
IPL750-4*		4	6.33	2.75	3.46	930-1178	3/8

## DUAL-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ITD-4	4 - 14	2	1.21	1.37	1.36	75-95	1/8
IPLD4-3		3	1.63	1.37	1.36	75-95	1/8
IPLD4-4		4	2.06	1.37	1.36	75-95	1/8
IPLD4-5		5	2.48	1.37	1.36	75-95	1/8
IPLD4-6		6	2.90	1.37	1.36	75-95	1/8
ITD-2	2 - 14	2	1.32	1.39	1.39	100-130	5/32
IPLD2-3		3	1.83	1.39	1.39	100-130	5/32
IPLD2-4		4	2.34	1.39	1.39	100-130	5/32
IPLD2-5		5	2.85	1.39	1.39	100-130	5/32
IPLD2-6		6	3.36	1.39	1.39	100-130	5/32
ITD-1/0	1/0 - 14	2	1.68	1.74	1.74	135-170	3/16
IPLD1/0-3		3	2.33	1.74	1.74	135-170	3/16
IPLD1/0-4		4	2.98	1.74	1.74	135-170	3/16
IPLD1/0-5		5	3.63	1.74	1.74	135-170	3/16
IPLD1/0-6		6	4.28	1.74	1.74	135-170	3/16
ITD-2/0	2/0 - 14	2	1.78	1.75	1.77	150-195	3/16
IPLD2/0-3		3	2.53	1.75	1.77	150-195	3/16
IPLD2/0-4		4	3.28	1.75	1.77	150-195	3/16
IPLD2/0-5		5	4.03	1.75	1.77	150-195	3/16
IPLD2/0-6		6	4.78	1.75	1.77	150-195	3/16
ITD-3/0	3/0 - 6	2	1.93	1.83	1.83	175-225	1/4
IPLD3/0-3		3	2.71	1.83	1.83	175-225	1/4
IPLD3/0-4		4	3.49	1.83	1.83	175-225	1/4
IPLD3/0-5		5	4.27	1.83	1.83	175-225	1/4
IPLD3/0-6		6	5.05	1.83	1.83	175-225	1/4
IPLD3/0-8		8	6.61	1.83	1.83	175-225	1/4
IPLD3/0-10		10	8.17	1.83	1.83	175-225	1/4
IPLD3/0-12		12	9.73	1.83	1.83	175-225	1/4
IT-250	250 - 6	2	2.15	2.28	2.29	230-290	5/16
IPLD250-3		3	3.01	2.28	2.29	230-290	5/16
IPLD250-4		4	3.88	2.28	2.29	410-527	5/16
IPLD250-5		5	4.74	2.28	2.29	410-527	5/16
IPLD250-6		6	5.60	2.28	2.29	615-790	5/16
IPLD250-8		8	7.32	2.28	2.29	820-1053	5/16
IPLD250-10		10	9.05	2.28	2.29	820-1053	5/16
IPLD250-12		12	10.77	2.28	2.29	820-1053	5/16
IPLD250-14		14	12.50	2.28	2.29	820-1053	5/16
IT-350	350 - 6	2	2.50	2.41	2.68	280-350	5/16
IPLD350-3		3	3.55	2.41	2.68	280-350	5/16
IPLD350-4		4	4.60	2.41	2.68	514-657	5/16
IPLD350-5		5	5.65	2.41	2.68	514-657	5/16
IPLD350-6		6	6.70	2.41	2.68	770-985	5/16
IPLD350-8		8	8.80	2.41	2.68	1028-1314	5/16
IPLD350-10		10	10.90	2.41	2.68	1028-1314	5/16
IPLD350-12		12	13.00	2.41	2.68	1028-1314	5/16

## DUAL-SIDE ENTRY CONT.

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IT-500	500 - 4	2	2.90	2.83	2.95	350-430	5/16
IPLD500-3		3	4.04	2.83	2.95	350-430	5/16
IPLD500-4		4	5.19	2.83	2.95	631-806	5/16
IPLD500-5		5	6.33	2.83	2.95	631-806	5/16
IPLD500-6		6	7.48	2.83	2.95	946-1209	5/16
IPLD500-8		8	9.77	2.83	2.95	1262-1612	5/16
IPLD500-10		10	12.06	2.83	2.95	1262-1612	5/16
IPLD500-12		12	14.35	2.83	2.95	1262-1612	5/16
IPLD500-14		14	16.64	2.83	2.95	1262-1612	5/16
IT-600	600 - 6	2	3.20	3.14	3.32	385-475	5/16
IPLD600-3		3	4.50	3.14	3.32	385-475	5/16
IPLD600-4		4	5.80	3.14	3.32	810-1035	5/16
IPLD600-5		5	7.10	3.14	3.32	810-1035	5/16
IPLD600-6		6	8.40	3.14	3.32	1215-1554	5/16
IPLD600-8		8	11.00	3.14	3.32	1620-2070	5/16
IPLD600-10		10	13.60	3.14	3.32	1620-2070	5/16
IPLD600-12		12	16.20	3.14	3.32	1620-2070	5/16
IT-750*	750 - 250	2	3.48	3.41	3.46	385-475	3/8
IPLD750-3*		3	4.90	3.41	3.46	385-475	3/8
IPLD750-4*		4	6.33	3.41	3.46	930-1178	3/8
IPLD750-6*		6	9.18	3.41	3.46	1395-1767	3/8
IPLD750-8*		8	12.03	3.41	3.46	1860-2356	3/8
IPLD750-10*		10	14.88	3.41	3.46	1860-2356	3/8
IPLD750-12*		12	17.73	3.41	3.46	1860-2356	3/8
IPLD750-14*		14	20.58	3.41	3.46	1860-2356	3/8

## DUAL-SIDE ENTRY, DOUBLE SCREW

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ITH-750**	750 - 1/0	2	3.48	4.47	3.31	435-535	5/16
IPLDH750-3**		3	4.90	4.47	3.31	435-535	5/16
IPLDH750-4**		4	6.33	4.47	3.31	930-1178	5/16
IPLDH750-5**		5	7.75	4.47	3.31	930-1178	5/16
IPLDH750-6**		6	9.18	4.47	3.31	1395-1767	5/16
IPLDH750-8**		8	12.03	4.47	3.31	1860-2356	5/16
IPLDH750-10**		10	14.88	4.47	3.31	1860-2356	5/16

## DUAL-SIDE ENTRY, STACKED DOUBLE ROW

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IPLDS350-4	350 - 6	4	2.50	3.91	3.75	514-657	5/16
IPLDS350-6		6	3.55	3.91	3.75	770-985	5/16
IPLDS350-8		8	4.60	3.91	3.75	1028-1314	5/16
IPLDS350-10		10	5.65	3.91	3.75	1028-1314	5/16
IPLDS350-12		12	6.70	3.91	3.75	1028-1314	5/16
IPLDS500-4	500 - 4	4	2.90	4.70	4.32	631-806	5/16
IPLDS500-6		6	4.04	4.70	4.32	946-1209	5/16
IPLDS500-8		8	5.19	4.70	4.32	1262-1612	5/16
IPLDS500-10		10	6.33	4.70	4.32	1262-1612	5/16
IPLDS500-12		12	7.48	4.70	4.32	1262-1612	5/16
IPLDS750-6*	750 - 1/0	6	4.90	4.97	4.96	1395-1767	3/8
IPLDS750-8*		8	6.33	4.97	4.96	1860-2356	3/8
IPLDS750-10*		10	7.75	4.97	4.96	1860-2356	3/8
IPLDS750-12*		12	9.18	4.97	4.96	1860-2356	3/8
IPLDS7502-1/010**	750 - 1/0	2	6.46	4.47	3.39	1860-2356	3/8
	1/0 - 14	10					3/16

## IN-LINE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ISR-1/0	1/0 - 14	2	3.23	0.96	1.74	135-170	3/16
ISR-250	250 - 6	2	3.95	1.21	2.29	230-290	5/16
ISR-350	350 - 6	2	4.47	1.33	2.68	280-350	5/16
ISR-500	500 - 4	2	5.37	1.46	2.95	350-430	5/16
ISR-600	600 - 6	2	6.10	1.77	3.32	385-475	5/16
ISRH-750**	750-1/0	2	7.26	2.83	3.31	435*535	5/16

## OFFSET ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ITO-4	4 - 14	2	1.21	1.37	1.36	75-95	1/8
ITO-1/0	1/0 - 14	2	1.68	1.74	1.74	135-170	3/16
ITO-3/0	3/0 - 6	2	1.93	1.83	1.83	175-225	1/4



## MOUNTABLE, SINGLE-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IPLM4-4	4 - 14	4	3.26	1.24	1.47	75-95	1/8
IPLM1/0-4	1/0 - 14	4	4.19	1.55	1.84	135-170	3/16
IPLM1/0-5		5	4.84	1.55	1.84	135-170	3/16

## MOUNTABLE, DUAL-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IPLMD3/0-3	3/0 - 6	3	3.95	1.83	1.95	175-225	1/4
IPLMD3/0-4		4	4.73	1.83	1.95	175-225	1/4
IPLMD3/0-5		5	5.51	1.83	1.95	175-225	1/4
IPLMD250-3	250 - 6	3	4.45	2.28	2.32	230-290	5/16
IPLMD250-4		4	5.32	2.28	2.32	410-527	5/16
IPLMD250-5		5	6.18	2.28	2.32	410-527	5/16
IPLMD250-6		6	7.04	2.28	2.32	615-790	5/16
IPLMD250-8		8	8.76	2.28	2.32	820-1053	5/16
IPLMD250-10		10	10.49	2.28	2.32	820-1053	5/16
IPLMD250-12		12	12.21	2.28	2.32	820-1053	5/16
IPLMD350-3	350 - 6	3	5.08	2.41	2.71	280-350	5/16
IPLMD350-4		4	6.13	2.41	2.71	514-657	5/16
IPLMD350-5		5	7.18	2.41	2.71	514-657	5/16
IPLMD350-6		6	8.23	2.41	2.71	770-985	5/16
IPLMD350-8		8	10.33	2.41	2.71	1028-1314	5/16
IPLMD350-10		10	12.43	2.41	2.71	1028-1314	5/16
IPLMD350-12	12	14.53	2.41	2.71	1028-1314	5/16	
IPLMD500-3	500 - 4	3	5.46	2.83	2.98	350-430	5/16
IPLMD500-4		4	6.61	2.83	2.98	631-806	5/16
IPLMD500-5		5	7.75	2.83	2.98	631-806	5/16
IPLMD500-6		6	8.90	2.83	2.98	946-1209	5/16
IPLMD500-8		8	11.19	2.83	2.98	1262-1612	5/16
IPLMD500-10		10	13.48	2.83	2.98	1262-1612	5/16
IPLMD500-12		12	15.77	2.83	2.98	1262-1612	5/16
IPLMD600-3	600 - 6	3	5.83	3.14	33.32	385-475	5/16
IPLMD600-4		4	7.13	3.14	33.32	810-1035	5/16
IPLMD600-5		5	8.43	3.14	33.32	810-1035	5/16
IPLMD600-6		6	9.73	3.14	33.32	1215-1554	5/16
IPLMD600-8		8	12.33	3.14	33.32	1620-2070	5/16
IPLMD600-10		10	14.93	3.14	33.32	1620-2070	5/16
IPLMD600-12	12	17.53	3.14	33.32	1620-2070	5/16	
IPLMD750-3*	750 - 250	3	6.28	3.41	3.48	385-475	3/8
IPLMD750-4*		4	7.71	3.41	3.48	930-1178	3/8
IPLMD750-6*		6	10.56	3.41	3.48	1395-1767	3/8
IPLMD750-8*		8	13.41	3.41	3.48	1860-2356	3/8
IPLMD750-12*		12	19.11	3.41	3.48	1860-2356	3/8

\* IT, IPL, IPLD, IPLDS, IPLMD - 750MCM connectors are rated AL7CU, 75°C

\*\* ITH, IPLH, IPLDH - 750MCM and IPLDS7502-1/010 connectors are rated AL90CU, 90°C

Scan for full  
installation  
instructions



## THE CHOICE IS CLEAR

Transparent pre-insulated connectors make it easy to see conductor placement, guaranteeing a high-quality connection. Key features include the comfortable ergonomic design, pre-filled oxide inhibitor and heavy-duty offerings rated for parallel runs. Usable on both line and load sides of an installation, Vision Tap is the most versatile multi-tap connector on the market.



## THE VISION TAP ADVANTAGE

### Clear Design

Visually confirm conductor placement for secure connections

### Removable plugs

Secures entry port closures and ensures debris prevention

### Smooth Exterior Finish

Ergonomic design is comfortable to grip when applying torque

### Pre-filled with Oxide Inhibitor

Corrosion prevention for low-contact resistance connections

### ●●● Parallel Rated and UL Listed

Multiple parallel configurations tested for maximum ampacities

See page 18 for a full listing of parallel rated connectors

## MULTIPLE CONFIGURATIONS

### SINGLE-SIDE ENTRY



### DUAL-SIDE ENTRY



### OFFSET ENTRY



### IN-LINE ENTRY



# POLARIS VISION TAP SPECIFICATIONS

## Wire Type

Use with Class B and C conductors

## Dual Rated

AL9CU, 90C\*

## UL Listed

UL486A/B for 600V max

## Location

Dry locations only

## Material

6061-T6 aluminum alloy

Insulated with high dielectric strength plastisol for increased chemical and abrasion protection

## Temperature

Cold rated to -45°C

WIRE CONNECTOR



## SINGLE-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IT-4C	4 - 14	2	1.21	1.24	1.36	75-95	1/8
IPL4-3C		3	1.63	1.24	1.36	75-95	1/8
IPL4-4C		4	2.06	1.24	1.36	75-95	1/8
IPL4-5C		5	2.48	1.24	1.36	75-95	1/8
IPL4-6C		6	2.90	1.24	1.36	75-95	1/8
IT-2C	2 - 14	2	1.32	1.24	1.39	100-130	5/32
IT-1/0C	1/0 - 14	2	1.68	1.55	1.74	135-170	3/16
IPL1/0-3C		3	2.33	1.55	1.74	135-170	3/16
IPL1/0-4C		4	2.98	1.55	1.74	135-170	3/16
IT-2/0C	2/0 - 14	2	1.78	1.55	1.77	150-195	3/16
IT-3/0C	3/0 - 6	2	1.93	1.60	1.83	175-225	1/4
IPL3/0-3C		3	2.71	1.60	1.83	175-225	1/4
IPL3/0-4C		4	3.49	1.60	1.83	175-225	1/4
IPL250-3C	250 - 6	3	3.01	2.01	2.29	230-290	5/16
IPL250-4C		4	3.88	2.01	2.29	410-527	5/16
IPL350-3C	350 - 6	3	3.55	2.13	2.68	280-350	5/16
IPL500-3C	500 - 4	3	4.04	2.500	2.95	350-430	5/16
IPL500-4C		4	5.19	2.500	2.95	631-806	5/16

## DUAL-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ITD-4C	4 - 14	2	1.21	1.37	1.36	75-95	1/8
IPLD4-3C		3	1.63	1.37	1.36	75-95	1/8
IPLD4-4C		4	2.06	1.37	1.36	75-95	1/8
IPLD4-5C		5	2.48	1.37	1.36	75-95	1/8
IPLD4-6C		6	2.90	1.37	1.36	75-95	1/8
ITD-2C	2 - 14	2	1.32	1.39	1.39	100-130	5/32
IPLD2-3C		3	1.83	1.39	1.39	100-130	5/32
IPLD2-4C		4	2.34	1.39	1.39	100-130	5/32
IPLD2-5C		5	2.85	1.39	1.39	100-130	5/32
IPLD2-6C		6	3.36	1.39	1.39	100-130	5/32
ITD-1/0C	1/0 - 14	2	1.68	1.74	1.74	135-170	3/16
IPLD1/0-3C		3	2.33	1.74	1.74	135-170	3/16
IPLD1/0-4C		4	2.98	1.74	1.74	135-170	3/16
IPLD1/0-5C		5	3.63	1.74	1.74	135-170	3/16
IPLD1/0-6C		6	4.28	1.74	1.74	135-170	3/16
ITD-2/0C	2/0 - 14	2	1.78	1.75	1.77	150-195	3/16
IPLD2/0-3C		3	2.53	1.75	1.77	150-195	3/16
IPLD2/0-4C		4	3.28	1.75	1.77	150-195	3/16
IPLD2/0-5C		5	4.03	1.75	1.77	150-195	3/16
IPLD2/0-6C		6	4.78	1.75	1.77	150-195	3/16
ITD-3/0C	3/0 - 6	2	1.93	1.83	1.83	175-225	1/4
IPLD3/0-3C		3	2.71	1.83	1.83	175-225	1/4
IPLD3/0-4C		4	3.49	1.83	1.83	175-225	1/4
IPLD3/0-6C		6	5.05	1.83	1.83	175-225	1/4
IT-250C	250 - 6	2	2.15	2.28	2.29	230-290	5/16
IPLD250-3C		3	3.01	2.28	2.29	230-290	5/16
IPLD250-4C		4	3.88	2.28	2.29	410-527	5/16
IPLD250-5C		5	4.74	2.28	2.29	410-527	5/16
IPLD250-6C		6	5.60	2.28	2.29	615-790	5/16
IPLD250-8C		8	7.32	2.28	2.29	820-1053	5/16
IT-350C	350 - 6	2	2.50	2.41	2.68	280-350	5/16
IPLD350-3C		3	3.55	2.41	2.68	280-350	5/16
IPLD350-4C		4	4.60	2.41	2.68	514-657	5/16
IPLD350-5C		5	5.65	2.41	2.68	514-657	5/16
IPLD350-6C		6	6.70	2.41	2.68	770-985	5/16
IPLD350-8C		8	8.80	2.41	2.68	1028-1314	5/16
IT-500C		500 - 4	2	2.90	2.83	2.95	350-430
IPLD500-3C	3		4.04	2.83	2.95	350-430	5/16
IPLD500-4C	4		5.19	2.83	2.95	631-806	5/16
IPLD500-5C	5		6.33	2.83	2.95	631-806	5/16
IPLD500-6C	6		7.48	2.83	2.95	946-1209	5/16
IPLD500-8C	8		9.77	2.83	2.95	1262-1612	5/16
IPLD500-10C	10		12.06	2.83	2.95	1262-1612	5/16
IT-600C	600 - 6	2	3.20	3.14	3.32	385-475	5/16
IPLD600-3C		3	4.50	3.14	3.32	385-475	5/16
IPLD600-4C		4	5.80	3.14	3.32	810-1035	5/16
IPLD600-5C		5	7.10	3.14	3.32	810-1035	5/16
IPLD600-6C		6	8.40	3.14	3.32	1215-1554	5/16
IPLD600-8C		8	11.00	3.14	3.32	1620-2070	5/16



## DUAL-SIDE ENTRY CONT.

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IT-750C*	750 - 250	2	3.48	3.41	3.42	385-475	3/8
IPLD750-3C*		3	4.90	3.41	3.42	385-475	3/8
IPLD750-4C*		4	6.33	3.41	3.42	930-1178	3/8
IPLD750-6C*		6	9.18	3.41	3.42	1395-1767	3/8
IPLD750-8C*		8	12.03	3.41	3.42	1860-2356	3/8

## IN-LINE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ISR-1/0C	1/0 - 14	2	3.23	0.96	1.74	135-170	3/16
ISR-250C	250 - 6	2	3.95	1.21	2.29	230-290	5/16
ISR-350C	350 - 6	2	4.47	1.33	2.68	280-350	5/16
ISR-500C	500 - 4	2	5.37	1.46	2.95	350-430	5/16
ISR-600C	600 - 6	2	6.10	1.77	3.32	385-475	5/16
ISRH-750C**	750 - 1/0	2	7.26	2.83	3.31	435-535	5/16

## OFFSET ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ITO-4C	4 - 14	2	1.21	1.370	1.36	75-95	1/8
ITO-1/0C	1/0 - 14	2	1.68	1.74	1.74	135-170	3/16
ITO-3/0C	3/0 - 6	2	1.93	1.83	1.83	175-225	1/4

\* IT, IPLD - 750MCM connectors are rated AL7CU, 75°C

\*\* ISRH-750MCM connector is rated AL90CU, 90°C

Scan for full  
installation  
instructions



## THE CHOICE FOR COPPER CONDUCTORS

Choose Polaris Grey when connecting fine-stranded, flexible or extra-flexible copper conductors. The ergonomic design, exceptional resistance to abrasion or chemicals and durable plastisol insulation make this a dependable, long-lasting connector that is easy to install. Save time and money on every job with the all-in-one design of Polaris pre-insulated connectors.



## TRUST IN GREY

### Designed for Copper

Use with fine-stranded, flexible and extra-flexible conductors

### Removable plugs

Secures entry port closures and ensures debris prevention

### Smooth Exterior Finish

Ergonomic design is comfortable to grip when applying torque

### Ferrule

Tin-plated ferrule captures and protects fine conductor strands

### Engineered to Last

Black insulation for a lifetime of exceptional UV resistance

## CONFIGURATION

### SINGLE-SIDE ENTRY



# POLARIS GREY SPECIFICATIONS

## Wire Type

Use with Class B, C, D, G, H, I, K, M and DLO copper conductors

## Copper wire only

9CU, 90C

## Material

6061-T6 aluminum alloy

Insulated with high dielectric strength plastisol for increased chemical and abrasion protection

## UL Listed

UL486A/B for 600V max

## Location

Dry locations only

## Temperature

Cold rated to -45°C

WIRE CONNECTOR



## SINGLE-SIDE ENTRY (BUILDING WIRE CLASS B, C, D)

CATALOG NUMBER	WIRE RANGE (AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (COPPER)	HEX KEY (IN.)
ITG-6	6 - 14	2	1.21	1.24	1.41	75	1/8
IPLG6-3		3	1.63	1.24	1.41	75	1/8
IPLG6-4		4	2.06	1.24	1.41	75	1/8
ITG-1	1 - 10	2	1.68	1.55	1.79	150	3/16
IPLG1-3		3	2.33	1.55	1.79	150	3/16
IPLG1-4		4	2.98	1.55	1.79	150	3/16
ITG-3/0	3/0 - 4	2	1.93	1.60	1.85	225	3/16
IPLG3/0-3		3	2.71	1.60	1.85	225	3/16
IPLG3/0-4		4	3.49	1.60	1.85	225	3/16

## SINGLE-SIDE ENTRY (FLEXIBLE WIRE CLASS G, H, I, K, M, DLO)

CATALOG NUMBER	WIRE RANGE (AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (COPPER)	HEX KEY (IN.)
ITG-6	6 - 14	2	1.21	1.24	1.41	75	1/8
IPLG6-3		3	1.63	1.24	1.41	75	1/8
IPLG6-4		4	2.06	1.24	1.41	75	1/8
ITG-1	2 - 10	2	1.68	1.55	1.79	150	3/16
IPLG1-3		3	2.33	1.55	1.79	150	3/16
IPLG1-4		4	2.98	1.55	1.79	150	3/16
ITG-3/0	2/0 - 2	2	1.93	1.60	1.85	225	3/16
IPLG3/0-3		3	2.71	1.60	1.85	225	3/16
IPLG3/0-4		4	3.49	1.60	1.85	225	3/16

Scan for full installation instructions



## EXTRA PROTECTION IN HARSH CONDITIONS

Polaris Edge is our toughest offering, designed for direct burial or temporary submersion and engineered to excel in those environments. Maintains a tight seal with trim-to-size wire port plugs and double o-rings on the screw port caps to ensure that no water or dirt infiltration interferes with your connection. When you need reliable performance, choose Polaris, the original innovator.



## DRY, WET OR BURIED

### Protected from the Elements

Temporary submersion up to 6' deep and direct burial applications

### Engineered to Last

Durable EPDM rubber insulation for abrasion and chemical resistance

### Removable plugs

Secures entry port closures and ensures debris prevention

### Pre-filled with Oxide Inhibitor

Corrosion prevention for low-contact resistance connections

## MULTIPLE CONFIGURATIONS

### SINGLE-SIDE ENTRY



### OFFSET ENTRY



### IN-LINE ENTRY





# POLARIS EDGE SPECIFICATIONS

## Wire Type

Use with Class B and C conductor stranding

## Dual Rated

AL9CU, 90C

## Material

6061-T6 aluminum alloy  
Insulated with high dielectric strength EPDM rubber for increased chemical and abrasion protection

## UL and ANSI Standards\*

ISPB2/0 Series and ISPBS350 in-line splice sizes meet or exceeds UL 486D and ANSI C119.1  
ISPB350 and ISPB600 sizes meet ANSI C119.1

## Location

Temporarily wet, dry and submersible locations

## Environmental

Sun and salt resistant

WIRE CONNECTOR



\*ISPB2/0 Series and ISPBS350 Series Only

## SINGLE-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ISPB2/0-2	2/0 - 14	2	1.93	2.66	2.11	150-195	3/16
ISPB2/0-3		3	2.79	2.66	2.11	150-195	3/16
ISPB2/0-4		4	3.65	2.66	2.11	150-195	3/16
ISPB2/0-6		6	5.37	2.66	2.11	150-195	3/16
ISPB350-3	350 - 12	3	3.61	4.14	3.06	280-350	5/16
ISPB350-4		4	4.80	4.14	3.06	514-657	5/16
ISPB350-6		6	7.18	4.14	3.06	770-985	5/16
ISPB600-3	600 - 12	3	4.87	5.43	3.80	385-475	5/16
ISPB600-4		4	6.56	5.43	3.80	810-1035	5/16
ISPB600-6		6	9.94	5.43	3.80	1215-1554	5/16

## OFFSET ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ISPB02/0	2/0 - 14	3	2.79	4.18	2.11	150-195	3/16

## IN-LINE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ISPBS2/0	2/0 - 14	2	5.05	0.88	2.10	150-195	3/16
ISPBS350	350 - 10	2	8.71	1.69	3.39	280-350	5/16

Scan for full installation instructions



# VISION TAP® & BLACK PARALLEL RATED

Polaris Vision Tap® and Black multi-tap connectors have high ampacity ratings, making them the only brand that can handle 4 parallel inputs. They're UL486A/B Listed for code compliance up to the maximum ampacity of copper and aluminum cables. For parallel runs done right, trust in Polaris.



WIRE RANGE (MCM/AWG)	IPL SERIES	IPLD SERIES	IPLMD SERIES	IPLDS SERIES	CU CONDUCTOR MAX AMPS	AL CONDUCTOR MAX AMPS
250-6	IPL250-4	IPLD250-4	IPLMD250-4	IPLDS250-4	527	410
	IPL250-4C	IPLD250-4C	-	-	527	410
	IPL250-5	IPLD250-5	IPLMD250-5	-	527	410
	-	IPLD250-5C	-	-	527	410
	IPL250-6	IPLD250-6	IPLMD250-6	-	790	615
	-	IPLD250-6C	-	-	790	615
	IPL250-8	IPLD250-8	IPLMD250-8	-	1053	820
	-	IPLD250-8C	-	-	1053	820
	-	IPLD250-10	IPLMD250-10	-	1053	820
350-6	IPL350-4	IPLD350-4	IPLMD350-4	IPLDS350-4	657	514
	-	IPLD350-4C	-	-	657	514
	IPL350-5	IPLD350-5	IPLMD350-5	-	657	514
	-	IPLD350-5C	-	-	657	514
	IPL350-6	IPLD350-6	IPLMD350-6	IPLDS350-6	985	770
	-	IPLD350-6C	-	-	985	770
	IPL350-8	IPLD350-8	IPLMD350-8	IPLDS350-8	1314	1028
	-	IPLD350-8C	-	-	1314	1028
	-	IPLD350-10	IPLMD350-10	IPLDS350-10	1314	1028
500-4	IPL500-4	IPLD500-4	IPLMD500-4	IPLDS500-4	806	631
	IPL500-4C	IPLD500-4C	-	-	806	631
	IPL500-5	IPLD500-5	IPLMD500-5	-	806	631
	-	IPLD500-5C	-	-	806	631
	IPL500-6	IPLD500-6	IPLMD500-6	IPLDS500-6	1209	946
	-	IPLD500-6C	-	-	1209	946
	IPL500-8	IPLD500-8	IPLMD500-8	IPLDS500-8	1612	1262
	-	IPLD500-8C	-	-	1612	1262
	-	IPLD500-10	IPLMD500-10	IPLDS500-10	1612	1262
600-6	IPL600-4	IPLD600-4	IPLMD600-4	-	1035	810
	-	IPLD600-4C	-	-	1035	810
	-	IPLD600-5	IPLMD600-5	-	1035	810
	-	IPLD600-5C	-	-	1035	810
	IPL600-6	IPLD600-6	IPLMD600-6	-	1554	1215
	-	IPLD600-6C	-	-	1554	1215
	-	IPLD600-8	IPLMD600-8	-	2070	1620
	-	IPLD600-10	IPLMD600-10	-	2070	1620
	-	IPLD600-12	IPLMD600-12	-	2070	1620
750-1/0	-	IPLDH750-4	-	-	1178	930
	-	IPLDH750-5	-	-	1178	930
	-	IPLDH750-6	-	-	1767	1395
	-	IPLDH750-8	-	-	2356	1860
	-	IPLDH750-10	-	-	2356	1860
	-	IPLDS7502-1/010	-	-	2356	1860

# POLARIS ACCESSORIES



CATALOG NUMBER	DESCRIPTION	CONNECTOR SIZE
SITG1	Grey Replacement Sleeve	1
SITG3/0	Grey Replacement Sleeve	3/0
SITG6	Grey Replacement Sleeve	6
SP4	Set-Screw Covers	4
SP1/0	Set-Screw Covers	1/0
SP2/0S	Edge Set-Screw Covers	2/0
SP3/0	Set-Screw Covers	3/0
SP250	Set-Screw Covers	250
SP350	Set-Screw Covers	350
SP350-ISP	Edge Set-Screw Covers	350
SP500	Set-Screw Covers	500
SP600	Set-Screw Covers	600
SP600S	Edge Set-Screw Covers	600
SP750	Set-Screw Covers	750
CP2/0S	Cable Port Plugs	2/0
CP3/0	Cable Port Plugs	3/0
CP250	Cable Port Plugs	250
CP350	Cable Port Plugs	350
CP350-ISP	Edge Cable Port Plugs	350
CP500	Cable Port Plugs	500
CP600	Cable Port Plugs	600
CP600-ISP	Edge Cable Port Plugs	600
CP750	Cable Port Plugs	750



## POLARIS CUSTOM

When you need something beyond the ordinary, turn to the Polaris Custom Connector program. Simply tell us your needs in a 4-step process, then let our engineers custom-build Polaris Black-style Connectors that are available quickly and UL-Listed for your specific applications.



Call our customer service team at 800-321-5847 for assistance in creating your own custom connector.

### What are the insulation needs?

We offer our extra-strength 6061-T6 aluminum connectors with or without high-performance plastisol insulation.



### What are the wire specifications?

The number, size and orientation of ports in your custom connector can be customized to your exact primary and secondary conductor specifications. Any wire size currently supported through existing Polaris families is available.



### Are there space restrictions?

We can stack wire entry holes to create a narrow connector that fits in small wireways or panels.

### Does the connector need to be mountable?

Mounting holes within the insulation sleeve are available if needed.

Visit [nsiindustries.com/polaris](http://nsiindustries.com/polaris) for information on connector torque values, wire strip lengths, and installation instructions.

